

XVR301-08T



Key Features

- 8-channel Video input
- Support CVBS, TVI, AHD, CVI & IP Cameras
- Support Cloud Storage for Snapshot over Drop Box or Google Drive
- 1 SATA Port, up to 8TB capacity
- Support 1CH Face Detection or 4CH Perimeter detection

| XVR301-08T | |
|----------------------|---|
| Operating System | Embedded Linux |
| Video/Audio Input | |
| Video Input | 8-ch |
| | CVBS, TVI, AHD, CVI Signal Adaptive Compatible, Access to the Optional IP Cameras |
| | BNC Interface (1.0Vp-p, 75 Ω) |
| | TVI4MP/AHD4MP/TVI3MP/AHD3MP/CVI3MP/TVI1080P/TVI720P/AHD1080P/AHD720P/CVI1080P/CVI720P/960H/DI |
| Network Video | 64Mbps |
| Audio Input | 1CH, RCA Interface (2 Vpp, 1k Ω) |
| Video/Audio Output | |
| CVBS Output | 1CH, BNC Interface (1.0Vp-p, 75 Ω) |
| VGA | 1CH, 1920x1080, 1280x1024, 1366x768, 1280x720, 1024x768 Resolution |
| HDMI | 1920x1080, 1280x1024, 1366x768, 1280x720, 1024x768 Resolution |
| Audio Output | 1-ch, RCA Interface |
| Intelligent Analysis | 1CH Face Detection or 4CH Perimeter detection |

| Video/Audio Encoding | |
|-----------------------------------|--|
| Real Time Monitor Resolution | Lite-4MP, 2048x1536, 1080P, 720p, WDI, D1 |
| Video Encoding | H.264 High Profile@ Level 14.2 |
| Encoding Resolution | Main Stream: Lite-4MP,3MP,1080P,720P, WDI, DI Auxiliary Stream: CIF, QCIF Option |
| Max Encoding Ability | 8 Ch 1080P@25FPS or 8CH 1080P@12FPS |
| Frame Rate | Lite-4MP,3MP, 1080P:1~12FPS; 720P/WD1/D1: 1~30FPS |
| Encoding Control | Qualified Rate, Variable Bit Rate Optional |
| Video Bit Rate | 32Kbps- 4096 Kbps |
| Stream Type | Composite/Video Streaming |
| Audio Encoding | G.711A |
| Audio Bit rate | 64Kbps |
| Dual stream | Support Up to CIF@30FPS |
| Video/Audio Decoding | |
| Video Encoding | H.264 High Profile @Level 14.2 |
| Synchronous Playback | Up to 8 CH |
| Max Decoding Ability | 8 Ch 720P@25FPS or 4Ch 1080P@12FPS |
| Other Function | |
| Motion Detection | 396 (22X 18) Detection Zones; Variable Sensitivity Levels |
| Regional Block | Support 4 Regional Block |
| Picture capture | Support JPEG Capture |
| HDD | |
| SATA | 1SATA Interface |
| Max capacity | Unlimited |
| External Interface | |
| Network Interface | 1RJ: 10M/100M Adaptive Ethernet Interface |
| USB | 2USB*2.0 Interface |
| Structure & Electrical Properties | |
| Dimensions | 250mmx235mmx45mm |
| Installation | Desktop Installation |
| Power | DC+12 V 2A |
| Working Temperature | 0 °C - ±55 °C |
| Working Humidity | 10%- ±90% |
| Consumption | 8W (Without HDD) |