

ANA3612T-PF28(36)(60)

2.0 Megapixel 1080P Plastic Dome Camera



Better Security,
Better World.



Main Features

- Hybrid Camera
- 2M High Definition
- 24 IR High Sensitive Led
- 3.6mm 2mega Fixed Lens
- Built-in IR-CUT, Low power consumption
- Support TVI AHD CVI and CVBS Hybrid output

Camera

| | |
|---------------------|---|
| Model | ANA3612T-PF36 |
| Image Sensor | 1/2.8" 2Megapixel High Definition Image Sensor |
| Image Resolution | PAL:25fps@1080P(1920x1080);NTSC:30fps@(1920x1080) |
| Effective Pixels | 1920(H)x1080(V),2.1MP |
| TV System | PAL/NTSC |
| Electronic Shutter | 1/25s-1/50.000s,1/30S~1/60,000S |
| Sync System | Internal |
| Usable Illumination | 0.01Lux |
| S/N Ratio | ≥50dB |
| Scanning System | TVI / AHD / CVI / CVBS |

Lens

| | |
|---------------|----------------------------|
| Focus Length | 2.8mm/3.6mm/6mm (optional) |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Pixels | 3M Pixels |

Night Vision

| | |
|-------------------|-------------------|
| Infrared LED | ∅ 5x24PCS |
| Infrared Distance | 20M |
| IR Status | Under 7Lux by CDS |
| IR Power On | CDS Auto Control |

Camera Features

| | |
|--------------------|-----------------------------------|
| Day/Night | Auto(ICR)/ Color /B&W |
| OSD Mesu Language | EN,CN,DE,FRA,IT,ES,PL,RU,PT,NL,TR |
| White Balance | Auto/Manual |
| Gain Control | Auto |
| Noise Reduction | 3D DNR |
| Picture Adjustment | Yes |
| OSD support | Yes |

General

| | |
|-----------------------|---------------------|
| IR Cut Filter | Yes |
| Heater | NO |
| Operation Temperature | -10℃~+50℃ Rh95% Max |
| Storage Temperature | -10℃~+50℃ Rh95% Max |
| Power Source | DC12V±10%, 500mA |