

# Network Video Recorder

## NVR202EP Series




### Key Features

- 8/16-channel input
- Third-party IP cameras supported with ONVIF conformance
- HDMI and VGA output up to 1080P
- Up to 4 Megapixels resolution recording
- Accurate retrieval, instant playback
- 2 SATA HDD up to 12 TB
- Plug & Play with up to 8 independent PoE network interfaces
- Support for P2P, UPnP, NTP, DHCP, PPPoE
- Support for mobile client access


## Specifications

	NVR202-08EP	NVR202-16EP
<b>Video and Audio</b>		
IP Video Input	8-ch	16-ch
Two-way audio Input	1-ch, RCA	
<b>Network</b>		
Incoming bandwidth	80Mbps	160Mbps
Outgoing bandwidth	96Mbps	
Remote connection	128	
<b>Video/Audio Output</b>		
HDMI/VGA Output	HDMI/VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz	
Recording Resolution	4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Audio Output	1-ch, RCA	
Synchronous Playback	8-ch	16-ch
<b>Decoding</b>		
Compression	H.264	
Live view/Playback	4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Capability	4 x 4MP@20, 6 x 1080p@25, 16 x 720p@25	
<b>Hard Disk</b>		
SATA	2 SATA interfaces	
Capacity	up to 6TB for each disk	
<b>External Interface</b>		
Network Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface	
Network Function	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P	
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0	
<b>PoE</b>		
Interface	8 independent 100 Mbps PoE network interfaces	
Supported Standard	IEEE 802.3at	
<b>General</b>		
Power Supply	52V DC	
Consumption ( without HDD and PoE )	≤ 8 W	
Working Temperature	-10°C ~ + 55°C ( +14°F ~ +131°F )	
Working Humidity	10% ~ 90%	
Dimensions	44 × 360 × 254mm ( 1.7" × 14.2" × 10.0" )	
Weight ( without HDD )	≤ 1.47 Kg ( 3.24 lb )	

## Dimensions



## Rear Panel



**Zhejiang Uniview Technologies Co., Ltd.**

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2011-2016 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.